













TSMG0216A GLASS DRILLING MACHINE



Throat depth: 1200mm (47 1/4")
 Hole diameter: 4-160mm (3/16" - 6 1/4")
 Glass Thickness: 3-30mm (1/8" - 1 3/16")
 Support table: 600mm x 500mm (24" x 20")
 Table height: 900mm (36")
 Weight: 850kg (1,870 LBS)
 Machine size 1950mm x 850mm x 1800mm
 (77" x 33" x 71")
 Support table: 2000mm x 1380mm x 850mm
 (78" x 55" x 33")
 Power: 220 Volt, 3 phase, 60 Hz
 Motors: 1.1 Kw x 2
 Air supply: 0.6 Mpa

Two 2-stepped vee belt pullys are installed on the motor shaft and drilling shaft. The motors have a 2-speed selector switch, so 4 drilling speeds can be obtained by changing belt position and selecting motor speed.
 The drilling depth is adjusted by rotating a graduated handwheel. An adjustable hydraulic damper is used to control the feed rate. The working or setup mode (automatic or semi automatic) can be selected at the control panel. The pressure of glass clamp and drill are adjustable.
 The bottom drilling is automatic, the top drilling can be automatic or manual with lever.
 A laser is used to align the hole for drilling.

TSMG0216A

 4-160mm	 3-30mm	 1200mm	 2.7	 2.6 x 2.0 x 1.8	 850kg
 4-160mm	 3-30mm	 850mm	 2.7	 1.6 x 0.75 x 1.8	 700kg

TSMG0216

“EXCLUSIVE NORTH AMERICAN AGENTS”



Tel: 800-971-8102 Fax: 951-734-0349
 E mail: sales@hilditchenterprises.com
 WEB: www.hilditchenterprises.com