



A uniquely engineered, low-maintenance, versatile design that will accommodate most cleaning applications in the small- to mid-range part sizes.

	Series	Conveyor Widths	Minimum Glass Size	Glass Thickness Range	Standard Operating Speed
	VC 20	20½"	4"-6"	0.039"–0.250" without adjustment 0.039"–0.375" with adjustment	Up to 50 ft./min.
	VC 24	24 ½"	4"-6"		
	VC 30	30½"	4"-6"		
	VC 36	36½"	6"		
	VC 40	40½"	6"		

Versatile Processing Capability —

engineered to simultaneously process both small- and mid-range part sizes

Flexible Design —

adapts to unique cleaning requirements

Quick-Maintenance Design —

provides for quick and easy part cleaning or replacement

Modular Construction —

interchangeable zones provide flexibility for custom arrangements or simplified future modifications

Standard 4-Corner Lift System —

ensures easy access for maintenance

Patented Quick-Release Bearing Design —


reduces bearing replacement and roll removal time



Included safety features not shown. Optional blower platform shown.

Versa Clean Series

KEY FEATURES





American Made



Customer Service



AVAILABLE OPTIONS:

Billco offers a wide range of optional features that permit the user to customize the washer to meet individual plant processing requirements and/or regulations. For a complete listing of all custom options available, please contact the Billco Sales Department.

- Non-Flat Part Processing Capability
- Fluidhead Rinse System
- Stainless Steel Frame
- Sound Reduction System
- Zero Consumption Water Saving System
- Prespray System
- Static Elimination System
- Low E Detection System
- Top Surface Oscillating Scrubber Section



Top Surface Oscillating Scrubber Section: Internal View



Solar Panels

WASHING APPLICATIONS INCLUDE:

- Solar Panels
- Touchscreens
- Automotive Mirrors
- Electronic Advertising
- Medical Applications



Billco Manufacturing, Inc. 100 Halstead Blvd., Zelienople, PA 16063 USA Phone: 724.452.7390 • Fax: 724.452.0217 sales@billco-mfg.com