



Designed for low- to mid-volume glass fabricators wishing to automate glass cleaning at a low capital investment.

PLC Touchscreen Control

System — provides easy operation and troubleshooting

Low E Compatible — meets most demanding processing requirements

Interface Capability —

compatible with downstream equipment control systems

Low Maintenance, FlipTop[™] Design — provides easy access

for maintenance

Stainless Steel Components -

offer enhanced corrosion resistance Included safety features not shown.

Conveyor Widths	Minimum Glass Size	Glass Thickness Range	Standard Operating Speed
36"	7"	0"– 0.250" Standard 0.250"– 0.750" (with optional Thickness Adjustment Cams)	10 ft./min.
48"	9½"		
60"	9½"		
72"	11½"		
84"	11½"		

Ideal For:

- > Custom and Replacement Insulating Window Producers
- Picture Frame or Other Specialty Glass Assembly Lines
- Secondary Manufacturing Lines for Special or Make-Up Work
- **Solar Applications**





KEY FEATURES

Maximum ROI









Customer Service



BillCO 24/7/365 Customer Service

AVAILABLE OPTIONS:

Billco offers a wide range of optional features that permit the user to customize the washer to meet individual plant processing requirements and/or regulations. For a complete listing of all custom options available, please contact the Billco Sales Department.

- Re-Circulating Rinse System
- Water Savings and Filtration Options
- Manual Hydraulic Top-Lift System
- Conveyor Deck Extensions
- Static Elimination System
- Thickness Adjustment Cams
- Low E Detection System
- Water Quality Monitoring

Included safety features not shown.



ATTRO



Billco Manufacturing, Inc. 100 Halstead Blvd., Zelienople, PA 16063 USA Phone: 724.452.7390 • Fax: 724.452.0217 sales@billco-mfg.com