



**HILDITCH ENTERPRISES, INC.**

**Glass Machinery Specialists**

2834 Hamner ave, #216

Norco, CA 92860

Tel: 951-734-0292

[www.hilditchenterprises.com](http://www.hilditchenterprises.com)

## **HEKKO-17 ROTATING SEALING STAND**

**( Power Rotating Cup / Telescoping Support Arms )**

- \* For Sealing Insulated Glass Units Vacuum Cup Size is 7" in diameter
- \* Variable Speed Rotational Control from 0 minimum to 5 maximum RPM
- \* Cup Frame Extendable from minimum 12" x 12" to maximum of 24" x 24" with a maximum diagonal distance across the frame of 40".
- \* Maximum recommended maximum sized IG Unit for sealing is 60" x 60".



**Hilditch Enterprises HEKKO -17 is an economical priced rotating cup sealing stand for speed of production and operator satisfaction. It can handle all types and sizes of IG Units and features nitrile ball casters to prevent glass units from scratching.**

## **HEKKO-17 Rotating Sealing Stand Technical Specifications**

### **Product Description**

The HEKKO-17 is a power operated stand used to facilitate the sealing of single insulating glass units up to 50 pounds in weight. The frame is constructed of heavy duty tubular aluminum extrusion that is topped with a upper telescoping frame upon which 4 swivel ball casters are mounted. The footprint size of the table is 42" x 42" upon which a rotating 7" diameter vacuum cup is mounted. The Vacuum cup support frame will retract to a minimum size of 16" x 16" and will extend to a maximum size of 24" x 24" with a diagonal support distance of 40". The minimum size IG unit that the table is capable of processing is 8" x 8" to a maximum size of 60' x 60".

The rotating vacuum cup is powered by a variable DC gear head motor with speed control. The vacuum cup rotation is actuated by an electrical foot pedal switch. Rotational speed is variable between 0 and 5 rpm. The cup frame is 34" high in its lowest position and can be adjusted to a maximum height of 36". The rotation is actuated by an electrical foot pedal. The vacuum source to the cup is actuated via a foot pedal switch. The HEKKO-17 Rotating Sealing Stand operates on 115 volt, 60 hz, single phase AC power with a minimum of 85 psi compressed air @ 2 cfm.

### **Advantages**

The sealant applicator can stand in one position and work at his own pace because of directional rotation and speed control. The table also has height adjustment for the comfort of the applicator.

### **Shipping Information**

Foot Print Size - 42" x 42"      Height - 34"      Weight - 175 Pounds

### **HEKKO-17 Rotating Sealing Stand**

<b><u>Description</u></b>	<b><u>Price</u></b>
HEKKO-17 Rotating Sealing Stand    ( Powered Rotation Model )	\$ 4,350.

Pricing is FOB Dallas, Texas. Sealing Stand is shipped in a totally enclosed wooden crate.